



Ultrarich and Effortlessly Luxe

SherShield Multakolor Stone Collection presents an exclusive finish that evokes the beauty of natural stones with rich, authentic character. Light is reflected and absorbed, transforming your home with luxurious texture and the sophisticated glamour.

DESCRIPTION

SherShield Multakolor Stone Collection is a water based, high-performance, stone effect coating for interior and exterior use.

- Durable, lightweight and cost-effective stone finish
- Suitable for many surfaces including concrete, masonry, plaster, gypsum board, wood, plastic, metals and pre-painted surfaces
- Excellent resistance to dirt, oil and household chemical (with clear coat option)
- Green technology - low VOC, low odour and non-toxic (lead-free, mercury-free, formaldehyde-free)
- Available in 12 standard colours. Colour matching and bespoke colours are also available (please contact us for more information).

CHARACTERISTICS

Gloss:	Flat
Coverage:	
Pattern close together:	9-18 sq.m
Pattern spread out:	18-40 sq.m
Drying Time @ 50% RH @ 25°C:	
To Touch:	3-5 hours
To Recoat:	24 hours
Packaging Size:	1 gallon

Suitable for healthcare facilities, schools, shopping centres, residential housing, offices, serviced apartments, hotels and resorts เหมาะสำหรับ โรงพยาบาล คลินิก โรงเรียน ศูนย์การค้า บ้าน ออฟฟิศ เซอร์วิสอพาร์ทเมนท์ โรงแรมและรีสอร์ท

**APPLICATION**

Application Temperature (Surface, Air, Substrate):	10-35°C
Relative humidity:	85% maximum
Applicator:	Airless Spray Pressure 2000 psi Tip 0.15"-0.19" Spray from left to right, Up to down
Reduction:	Maximum 5% if needed
Clean Up:	Water

PAINT SYSTEMS**Concrete, masonry, plaster, gypsum board**

1 coat: Sherwin-Williams Ultra Premium Exterior Acrylic Primer, B49W22 @ 30 microns DFT per coat by spray/brush/roller

2 coats: Sherwin-Williams Duracraft Exterior Acrylic Satin, C7 Series @ 30 microns DFT per coat by spray/brush/roller

1 coat: SherShield Multakolor Stone Collection, OM Series by spray

1-2 coats: Sherwin-Williams All Surface Enamel Clear Flat, A41-1400-C101 by spray/brush/roller

or 1-2 coats: Sherwin-Williams All Surface Enamel Clear Satin, A41-1300-C101 by spray/brush/roller

or 1-2 coats: Sherwin-Williams All Surface Enamel Clear Hi-Gloss, A41-1200-C101 by spray/brush/roller

or 1-2 coats: Sherwin-Williams Hi-Solids Polyurethane Clear Flat

or 1-2 coats: Sherwin-Williams Hi-Solids Polyurethane Clear Gloss

APPLICATION

- When mixing the paint, shake gently for 10 minutes. Do not stir.
- Do not add more than 5% of water
- Leftover paint must be discarded. Do not pour back into the container
- Store paint in temperature between 15-35°C
- Work in well ventilated area
- Keep away from children
- Clean the spray filter thoroughly after use with water

SURFACE PREPARATION

Surface must be dry and clean

Suitable for healthcare facilities, schools, shopping centres, residential housing, offices, serviced apartments, hotels and resorts เหมาะสำหรับ โรงพยาบาล คลินิก โรงเรียน ศูนย์การค้า บ้าน ออฟฟิศ เซอร์วิสอพาร์ทเมนท์ โรงแรมและรีสอร์ท